



UL 752 Specifications and Ammunition

Rating	Ammunition	Grain	(g)	Minimum fps	Velocity m/s	shots fired	paragraph
Level 1	9 mm full metal copper jacket with lead core	124	8	1175	358	3	4.3
Level 2	.357 Magnum jacketed lead soft point	158	10.2	1250	381	3	4.4
Level 3	.44 Magnum lead semi wad-cutter	240	15.6	1350	411	3	4.5
Level 4	.30 Caliber rifle lead core	180	11.7	2540	774	1	4.6
Level 5	7.62 mm rifle lead core full metal copper jacket military ball	150	9.7	2750	838	1	4.7
Level 6	9 mm full metal copper jacket with lead core	124	8	1400	427	5	4.8
Level 7	5.56 mm rifle full metal copper jacket with lead core	55	3.56	3080	939	5	4.9
Level 8	7.62 mm rifle lead core full metal copper jacket, military ball	150	9.7	2750	838	5	4.1
Supplementary Shotgun	12-Gauge rifled lead slug and	437	28.3	1585	483	3	4.11
	12-Gauge 00 lead buck shot (12 pellets)	650	42	1200	366		

Maximum Velocity is 110 percent of minimum velocity.

Paragraphs are listed in "UL 752 Paragraphs Page"

note: when printing, be sure to print in "Landscape" mode for best results